

**INQUIRIES?**

PHONE 1.810.629.6663

FAX 1. 810.629.8145

WEB ATLASTECHNOLOGIES.COM

EMAIL SALES@ATLASTECHNOLOGIES.COM

## PRODUCT DETAILS

## FLEX 3000 In-Press Transfer System

Atlas Technologies' FLEX 3000 In-press Transfer System is high speed and fully programmable. The FLEX 3000 can be easily retrofitted to existing presses or integrated with new presses. This system is the perfect unit for parts and tooling under 600 pounds.

**BELOW**

The Atlas FLEX 3000 Transfers parts for a Michigan based Tier 1 stamper.



## BENEFITS

**HIGHER PRODUCTIVITY**

Since the transfer path is fully programmable, presses can run smaller parts faster than a cam actuated transfer. Smoother transfer also allows faster speeds without loss of part control.

**FAST CHANGEOVER**

**Optional Feature** - Changeover is as simple as calling up a stored program at the control panel and connecting two finger tooling rails.

**DIE ACCESSIBILITY**

Dies are easily accessed, since the FLEX 3000 is mounted overhead and the finger tooling rails can be raised completely out of the way.

**RELIABILITY AND MAINTAINABILITY (R&M)**

Proven servo-drive, low inertia design and fewer elements to wear result in higher R&M.

**UTILIZING EXISTING ASSETS**

A FLEX 3000 transfer system combined with an existing press costs much less than a new transfer press.

**DUAL PITCH CAPABILITY**

By splitting the long axis into two separate units and drives, it is now possible to have two separate pitches and accommodate conditions where the pitch could be longer on the first group of dies within the press and shorter for smaller dies.

**TOP LEFT**

A Canadian Tier 1 Stamper is able to take on additional work due to their Atlas FLEX 3000 with Universal Rails and FLEX Finger Tooling.

**BOTTOM**

Atlas Universal Rails allow quick tooling changeover.

## STRENGTH, SPEED, POWER, AGILITY AND AMBITION... IT MUST BE A FLEX

- + Tri-axis, dual-axis, cross-bar or forward/reverse modes of operation
- + Extruded low-mass aluminum rails allow for high-speed operations
- + Transfer rails are supported along the length of the rail, instead of at the ends, for higher rigidity and less deflection
- + Anti-backlash couplings improve accuracy and smoothness, while reducing wear
- + Overhead mounted design:
  - Easy, open access to the dies
  - Bolster is open for scrap removal
  - Windows are clear for part feeding
- + Transfer path corner radii programmability
- + Jog capability (forward and reverse) is independent of press actuation
- + Fully programmable part sensing
- + PC-based remote access diagnostics via modem

## OPTIONS

- + Die automation control package
- + External lift unit to clear tall dies
- + Live camera for remote access
- + FLEX Finger Tooling.
- + Dual transfer pitch capability
- + Transfer Hand Held Teach Pendant
- + Increased part & tooling weight capacity of 750 lbs. (340 kg)

## SPECIFICATIONS

**TRANSFER STROKE**

0-84" (2135 MM)

**POSITION ACCURACY**

0.002" (0.05 MM)

**X-AXIS SPEED**

560 FT./MIN. (170 M/MIN)

**CLAMP STROKE**

0-36" (915 MM)

**POSITION ACCURACY**

0.001" (0.025 MM)

**Y-AXIS SPEED**

305 FT/MIN (93 M/MIN)

**LIFT STROKE**

0-30" (760 MM)

**POSITION ACCURACY**

0.001" (0.025 MM)

**Z-AXIS SPEED**

230 FT/MIN (70 M/MIN)

**STANDARD PART & TOOLING WEIGHT**

600 LBS. (272 KG)

**NUMBER OF DIE STATIONS**

12 STANDARD

**SINGLE RAM PRESS**

16+ OPTIONAL

**TOOLING**

DEDICATED RAILS WITH SEMI-AUTO CONNECTIONS